

Liftronic® Mobile

The Intelligent Device
for Handling you
can easily move
wherever you need



Advantages

- ✓ Designed to be safely and easily mounted on an electric pallet truck
- ✓ Easy and safe to move around
- ✓ Easy interchange of grippers for handling different type of load
- ✓ Easy battery replacement

Safeties



Acoustic alarm

If the arm is not secured when moving the pallet truck, a sensor activates an acoustic alarm



Arm

In case of rope damage a mechanical safety device prevents the arm from lowering



Battery


If batteries are low, the system allows the arm to be moved to a rest or unload position; a low battery message will then be displayed



Switch-off

In case of accidental switch-off, the system allows arm to be moved to a rest or unload position

Suitable for different load grippers:



Very agile



Precise




Ergonomic



Zero gravity


4 JOINTS

3 on the arm + 1 on the gripper coupling




ORIENTATION

On the left or on the right according to the work area side



SWIVEL JOINT

On the end of arm for continuous rotation around the gripper axis



Technical data

- Gross load capacity: 60 kg (including gripper)
- Arm length: 2530 mm
- Vertical stroke: 1500 mm- sliding on a column
- Autonomy: up to 6 hours for a continuous cycle
- Overall size: 920 x 890 x 2300 mm
- Vacuum gripper: air through the arm, no pipes